



## FEATURES




- Low Profile DFN 2.0x2.0x0.62 mm for Board Space Saving
- Ultra Low RDS(on)
- This is a Pb-Free Device
- We declare that the material of product are Halogen Free and compliance with RoHS requirements.

## APPLICATIONS

- Battery Switch
- High Side Load Switch

## ORDERING INFORMATION

Device	Marking	Shipping
LXP1220C	32	4000/Tape&Reel



Pin1

32 = Device Code  
Y = Date Code\*

## MAXIMUM RATINGS(Ta = 25°C unless otherwise stated)

Parameter	Symbol	Limits	Unit
Drain-to-Source Voltage	VDSS	20	V
Gate-to-Source Voltage	VGS	±10	V
Drain Current (Note 1) Steady State	ID	12	A
Pulsed Drain Current (tp = 10 μs)	IDM	35	A
Power Dissipation (Note 1)			
Steady State	PD	1.6	W
t < 7 s		3.0	
Operating Junction and Storage Temperature Range	TJ , TSTG	-55~+150	°C
Lead Temperature for Soldering Purposes (1/8 " from case for 10 s)	TL	260	°C
Gate-Source ESD Rating (HBM, Method 3015)	ESD	2000	V

1. Surface-mounted on FR4 board using 1 in sq pad size (Cu area = 1.127 in sq [1 oz] including traces)




## ELECTRICAL CHARACTERISTICS

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>NMOSFET</b>						
Drain-Source Breakdown Voltage	V(BR)DSS	VGS = 0 V, ID = 250 $\mu$ A	-20			V
Drain-to-Source Breakdown Voltage Temperature Coefficient	V(BR)DSS /TJ			10		mV/°C
Zero Gate Voltage Drain Current	IDSS	VGS = 0 V, VDS = -20 V, TJ = 25°C			-1	$\mu$ A
Gate-to-Source Leakage Current	IGSS	VDS = 0 V, VGS = $\pm$ 5 V			$\pm$ 5	$\mu$ A
Gate Threshold Voltage (Note2)	VGS(TH)	VGS = V DS, ID = 250 $\mu$ A	-0.4		-1	V
Negative Threshold Temperature Coefficient (Note2)	VGS(TH) /TJ			3.0		mV/°C
Drain-to-Source On Resistance (Note2)	RDS(on)	VGS = -4.5 V, ID = -6A		16	19	m $\Omega$
		VGS = -2.5 V, ID = -4 A		22	34	
		VGS = -1.8 V, ID = -3 A		31	42	
Forward Transconductance (Note2)	gFS	VDS = -5 V, ID = -3A		40		S
Input Capacitance	CISS	VGS = 0 V, f = 1 MHz, VDS = -15 V		2240		pF
Output Capacitance	COSS			240		
Reverse Transfer Capacitance	CRSS			210		
Total Gate Charge	QG(TOT)	VGS = -4.5 V, VDS = -15 V; ID = -4A		28		nC
Threshold Gate Charge	QG(TH)			1.0		
Gate-to-Source Charge	QGS			2.9		
Gate-to-Drain Charge	QGD			8.8		
Turn-On Delay Time (Note3)	td(ON)	VGS = -4.5 V, VDD = -15 V; ID = -4A, RG = 1 $\Omega$		8.6		ns
Rise Time (Note3)	tr			15		
Turn-Off Delay Time (Note3)	td(OFF)			150		
Fall Time (Note3)	tf			88		
Forward Diode Voltage	VSD	VGS = 0 V, IS = -1A	TJ = 25°C	0.63	1	V
			TJ = 125°C	0.5		


2. Pulse Test: pulse width  $\leq$  300  $\mu$ s, duty cycle  $\leq$  2%

3. Switching characteristics are independent of operating junction temperatures


**ELECTRICAL CHARACTERISTICS CURVES**




**On-Region Characteristics**



**Transfer Characteristics**




**On-Resistance vs. Gate-to-Source Voltage**




**On-Resistance vs. Drain Current and Gate Voltage**




**ELECTRICAL CHARACTERISTICS CURVES (Con.)**




**On-Resistance Variation with Temperature**



**Drain-to-Source Leakage Current vs. Voltage**




**Diode Forward Voltage vs. Current**




**Threshold Voltage**


**ELECTRICAL CHARACTERISTICS CURVES (Con.)**



**Gate-to-Source and Drain-to-Source Voltage vs. Total Charge**




**Capacitance variation**




**FET Thermal Response**

**OUTLINE AND DIMENSIONS**



DFN2020-6S			
DIM	MIN	NOR	MAX
A	0.45	0.58	0.65
A1	0.01	0.03	0.05
b	0.25	0.30	0.35
D	1.95	2.00	2.05
E	1.95	2.00	2.05
e	0.65TYP.		
L	0.23	0.28	0.33
L1	0.60	0.65	0.65
D1	0.90	0.95	1.00
E1	1.10	1.15	1.20
A3	0.152REF		
All Dimensions in mm			

**SOLDERING FOOTPRINT**



DFN2020-6S	
Dim	(mm)
X	0.40
X1	0.95
X2	1.70
e	0.65
Y	0.43
Y1	0.75
Y2	1.15
Y3	1.54
Y4	2.39